QUICK INTERLOCK

QUICK INTERLOCK VALVE

Edition. 21.0

Stainless Steel

- Type: Quick Interlock Valve
- Models: Ball Valve for cooling
- Sizes: from DN25 to DN50
- Pressure: PN16

MAIN BENEFITS

- **Twin Identical Parts**
  Featuring identical coupling halves, this design requires only one part number, simplifying orders and inventory handling.

- **Swivel Closure Ends**
  The swivel ends prevent hose twisting during installation and operation, ensuring longer hose life and easier handling.

- **Safety Coupling Mechanism**
  The valves only open when fully connected and can only be disconnected after both sides are securely closed, eliminating the risk of accidental disconnection, leakage, or fluid spills.

- **Extra Safety: Remote Monitoring & Enhanced Security**
  Optional integration of a proximity sensor allows remote supervision. In case of tampering or unintended disconnection, the system immediately sends a warning signal, providing an extra layer of safety.

- **316 Stainless Steel Construction**
  Robust and corrosion-resistant, ideal for demanding industrial environments.

MAX. WORKING PRESSURE:
1.6 MPA (232 PSI)

QUICK INTERLOCK VALVE DIN/ISO 228 BSP

TYPE	DN	PN			A	C	G	H	I	ØM	ØLW	WEIGHT	
Quick Interlock Valve G 1	25	MPa	1,6	mm	62	75	42	56	75	G 1	20	kg	0,719
		Psi	232	inch	2,44	2,95	1,65	2,20	2,95		0,79	lb	1,59
Quick Interlock Valve G 2	50	MPa	1,6	mm	103	115	72	56	110	G 2	39	kg	2,506
		Psi	232	inch	4,06	4,53	2,83	2,20	4,33		1,54	lb	5,52



QUICK INTERLOCK VALVE ANSI/ASME B1.20.1 NPT

TYPE	DN	PN			A	C	D	E	F	ØM	ØLW	WEIGHT	
Quick Interlock Valve N 1	25	MPa	1,6	mm	62	75	42	56	75	N 1	20	kg	0,719
		Psi	232	inch	2,44	2,95	1,65	2,20	2,95		0,79	lb	1,59
Quick Interlock Valve N 2	50	MPa	1,6	mm	103	115	72	56	110	N 2	39	kg	2,506
		Psi	232	inch	4,06	4,53	2,83	2,20	4,33		1,54	lb	5,52



QUICK INTERLOCK VALVE SAE J1926-1

TYPE	DN	PN			A	C	D	E	F	ØM	ØLW	WEIGHT	
Quick Interlock Valve SAE16	25	MPa	1,6	mm	62	75	42	56	75	1 5/16-12 UN	20	kg	0,719
		Psi	232	inch	2,44	2,95	1,65	2,20	2,95		0,79	lb	1,59
Quick Interlock Valve SAE32	50	MPa	1,6	mm	103	115	72	56	110	2 1/2 - 12 UN	39	kg	2,506
		Psi	232	inch	4,06	4,53	2,83	2,20	4,33		1,54	lb	5,52